

M-735 Monitor (7")

DESCRIPTION

This Professional 7" Monitor features a high resolution super bright (450 cd/m²) TFT LCD panel. This monitor boasts a highly efficient housing design that provides for very slim and compact monitor

Also features built in speaker; clip on sun visor; pedestal mount and remote control.

Suitable for all vehicles and mobile plant 12-24 volt application.

KEY FEATURES

- 7.0 inch Colour Digital wide-screen Monitor
- Slim-line soft touch casing
- Pedestal mount
- Trigger wires for auto switching of individual cameras
- Selectable Reversing Grid
- Picture adjustable in horizontal, vertical and mirror orientations
- Clip on sun visor
- Remote control
- All materials and PCB production conform to RoHS standard
- Available with Waterproof or Slim line AV connectors on monitor harness



RoHS

SPECIFICATION

Monitor Type	TFT Analogue LCD
Screen Size / Ratio	7" (176.2mm) / 16:9
Resolution	1440(H) x 234(V) (480x 3 RGB x 234)
Contrast	300:1
Brightness	450 cd/m ²
Viewing Angle	60 degrees
Video Format	Selectable Auto/ PAL / NTSC
AV Connections	2 x AV in, 1 x V out
Power Out	Reg. 12Volts for cameras through AV Connectors
Speaker	1 Watt output
Power Consumption	7 Watts
Operating Voltage	9-36 volts
Operating Temp.	-20 deg to 85 deg C, 90%RH
Size	170mm(W)x 115mm(H)x 20mm(D)
Weight	0.35 Kg